



Australian Government

CPCCE3014 Remove non-friable asbestos

Release: 2

CPCCE3014 Remove non-friable asbestos

Modification History

Release 2 This version first released with CPC Construction, Plumbing and Services Training Package Release 5.1.

Rectified pre-requisite unit.

Release 1 This version first released with CPC Construction, Plumbing and Services Training Package Release 5.0.

Supersedes and is equivalent to CPCCE3014A Remove non-friable asbestos.
Updated to meet the Standards for Training Packages 2012.

Application

This unit of competency specifies the outcomes required to remove non-friable asbestos containing material (ACM).

It includes preparing, containing and removing non-friable ACM, and knowledge of decontamination and disposal requirements.

Site location can be a real workplace or simulated environment that may include domestic or commercial premises, a demolition site, a new worksite or an existing structure being renovated, extended, restored or maintained.

Project sites for removal of non-friable asbestos include construction sites, ships and soils.

The model work health and safety (WHS) regulations and the Code of Practice: How to safely remove asbestos (2018) requires workers to hold certification for the class of licensed asbestos removal work they will be undertaking. Completion of this unit of competency is certification to undertake non-friable (Class B) removal work.

Occupational licenses are required nationally. This unit is required for all ACM removal workers engaged in the removal of more than ten square metres of non-friable ACM.

Candidates are advised to consult with the relevant state and territory regulatory authorities to confirm specific jurisdictional licensing requirements to remove non-friable ACM.

Pre-requisite Unit

CPCCWHS1001 Prepare to work safely in the construction industry

Unit Sector

Demolition

Elements and Performance Criteria

Elements describe the essential outcomes.

Performance criteria describe what needs to be done to demonstrate achievement of the element.

- | | |
|----------------------------------|--|
| 1 Prepare for asbestos removal. | <p>1.1 Obtain work instructions and participate in review of asbestos removal control plan (ARCP) and safe work method statements (SWMS).</p> <p>1.2 Gather safety requirements and data from an on-site assessment and asbestos register where available.</p> <p>1.3 Use information sources to ensure the ARCP and SWMS are site-specific for the removal of asbestos materials.</p> <p>1.4 Select tools, equipment and personal protective equipment (PPE) consistent with job requirements to carry out tasks, check for serviceability, and rectify or report faults prior to commencement.</p> <p>1.5 Notify regulator, occupants, neighbours and other affected parties according to legislation and within limits of own responsibility and code of practice.</p> <p>1.6 Contribute to the preparation and use of an emergency plan, within limits of own responsibility and according to legislative and company requirements.</p> <p>1.7 Contribute to processes required to undertake air monitoring and to meet health monitoring requirements in line with level of authority and responsibility and regulatory requirements.</p> |
| 2 Prepare asbestos removal site. | <p>2.1 Identify location of non-friable asbestos materials and confirm with supervisor location of site boundaries.</p> <p>2.2 Implement signage and barricade requirements to delineate the asbestos removal site according to ARCP.</p> <p>2.3 Prepare and place materials and equipment required for removal of ACM from site.</p> |
| 3 Set up asbestos work area. | <p>3.1 Designate boundaries of asbestos work area according to ARCP requirements.</p> <p>3.2 Set up decontamination according to ARCP.</p> |

- 3.3 Set up asbestos waste storage and waste transit route according to ARCP.
 - 3.4 Undertake processes to ensure the safety of the site, including deactivating or securing utilities where necessary prior to commencing work.
- 4 Remove non-friable asbestos.
 - 4.1 Fit-check respiratory protective equipment (RPE) and fit PPE.
 - 4.2 Wet down or spray work area with particle binder.
 - 4.3 Carry out asbestos removal ensuring airborne asbestos fibres are kept to a minimum (i.e. appropriate tools, wet removal, minimise breakage, good handling techniques).
 - 4.4 Contain, wrap or otherwise seal the wet asbestos, place into removal bags or bins, seal and label according to ARCP.
- 5 Carry out decontamination process.
 - 5.1 Carry out decontamination of the work area and tools according to ARCP.
 - 5.2 Carry out personal decontamination according to ARCP.
- 6 Clean up work area.
 - 6.1 Remove asbestos waste materials and equipment from the area according to ARCP.
 - 6.2 Store tools, plant and equipment according to manufacturer recommendations and regulatory requirements to ensure site is ready for clearance inspection.
 - 6.3 Take steps to ensure clearance inspection requirements are met, within the limits of own responsibility and to ensure clearance certificate is gained from a competent person or licensed asbestos assessor.
- 7 Complete regulatory processes
 - 7.1 Ensure clearance inspection is undertaken prior to removing signage, plant and equipment.

- 7.2 Contribute to the preparation and use of documentation for regulatory notification processes, within limits of own responsibility and according to legislative and company requirements.
- 7.3 Provide stakeholders with clearance inspection certificate prior to reoccupation, as required.

Foundation Skills

Foundation skills essential to performance are explicit in the performance criteria of this unit of competency.

Unit Mapping Information

Supersedes and is equivalent to CPCCE3014A Remove non-friable asbestos.

Links

Companion volumes to this training package are available at the VETNet website - <https://vetnet.gov.au/Pages/TrainingDocs.aspx?q=7e15fa6a-68b8-4097-b099-030a5569b1ad>