

Australian Government

Department of Education, Employment and Workplace Relations

DEFDV013B Employ air-lift devices underwater

Release: 1



DEFDV013B Employ air-lift devices underwater

Modification History

Not applicable.

Unit Descriptor

| Unit Descriptor | This unit covers the competency required to move submerged objects using air-lift devices (i.e. bags). |
|-----------------|--|
| | The unit includes selecting and inspecting the bags appropriate to the lift, securing the bags to the object and inflating the bags to the required buoyancy in order to manoeuvre the object under control. Attention must be given to safety of other divers and nearby vessels and/or structures during work, as well as consideration for the environment. |
| | Note: This Unit of Competency relates, in part, to the existing standards of the Australian Diver Accreditation Scheme (ADAS). All information was correct at the time of development of this Unit of Competency; however, any diver seeking ADAS accreditation should consult ADAS and not rely on the information contained in this unit. |

Application of the Unit

Application of the UnitThe application of this unit in the workplace - the
environments, complexities and situations involved -
will be written during Phase II of the Review of the
PUA00 Public Safety Training Package.

This text will be useful for the purposes of job descriptions, recruitment advice or job analysis; where possible, it will not be too job specific to allow other industries to import it into other Training Packages, where feasible.

Licensing/Regulatory Information

Not applicable.

Pre-Requisites

| Prerequisite Unit/s | DEFDV001B Dive using self contained underwater breathing apparatus in open water to 30 metres |
|---------------------|--|
| | DEFDV016B Perform underwater rigging work |

Employability Skills Information

Employability Skills This unit contains employability skills.

Elements and Performance Criteria Pre-Content

| | Performance Criteria describe the required performance needed to demonstrate achievement of the element. Where bold italicised text is used, further information is detailed in the Required Skills and Knowledge and/or the Range Statement. Assessment of performance is to be consistent with the Evidence Guide. |
|--|---|
|--|---|

Elements and Performance Criteria

ELEMENT

1. Prepare for underwater air-lift operation

2. Operate air-lift devices

3. Conclude air-lift operations

PERFORMANCE CRITERIA

- 1.1 *Load metrics* and *worksite data* are determined and analysed to determine the specific requirements for the air-lift bags
- 1.2 Work plan is developed consistent with the dive plan
- 1.3 Air-lift bags are *selected*, *inspected* and *prepared*
- 1.4 Air-lift bags are secured safely to/from the dive site
- 1.5 Access obstructions and other hazards are assessed and *action* is taken to *remove/reduce the risk*
- 2.1 Air-lift bags are secured to the object's lift point/s
- 2.2 A work-safe area is established and the location and safety of divers is confirmed prior to commencing the lift
- 2.3 Air-lift bags are inflated and adjusted to control buoyancy
- 2.4 Movement of the object is *effectively controlled*
- 3.1 *Environmental impact* arising from the work task is minimised and waste products are recovered
- 3.2 Air-lift bags are de-rigged from the object
- 3.3 Air-lift bags are *de-serviced* and stored for re-use

Required Skills and Knowledge

REQUIRED SKILLS AND KNOWLEDGE

This describes the essential skills and knowledge and their level, required for this unit.

Required Skills

- check equipment
- control neutrally buoyant objects
- inflate air-lift bags
- inspect equipment for serviceability and functionality
- planning
- rig equipment

Required Knowledge

- characteristics and employment of air-lift bags
- determination of mass of submerged objects
- dive equipment
- dive physics
- general occupational/diving safety awareness
- marine hazards
- oceanography
- relevant references and Australian Standards

Evidence Guide

Critical aspects for assessment and evidence required to demonstrate competency in this unit

Context of and specific resources for assessment

Assessment must confirm the ability to attend to personal and collective safety; and to consider the environmental impact as part of the dive plan.

Consistency in performance

Competency should be demonstrated during the following air-lift operations with manually inflated air-bags:

- 1 x vertical lift to surface
- lift distance at least 5 metres (object must breach surface)
- depth between 5 to 20 metres
- weight at least 250 kg
- 1 x lateral lift
- lateral distance at least 10 metres
- depth between 5 to 20 metres
- weight at least 250 kg.

Context of assessment

Competency should be assessed in the ocean.

When practicable, assessment should relate to the diver's vocational focus.

Specific resources for assessment

Access to a complete range of diving, safety and accessory equipment; air-lift equipment; and submerged objects.

Range Statement

RANGE STATEMENT

The Range Statement relates to the Unit of Competency as a whole. It allows for different work environments and situations that may affect performance. *Bold italicised* wording in the Performance Criteria is detailed below.

ī

| CompositionDimensionsLift pointsWeightCurrentDepthGradientHazardsObstaclesDistaclesSelecting, inspecting and mcludePreparing air-lift bags may includePreparing air-lift bags may mcludePreparing air-lift bags may mcludePreparing air-lift bags may mcludeChecking attachment lines and points inspecting the neck inspecting the outer skin Test fillPreferively controlling the poincludeBoth lateral and vertical adjustments (Sing patrol/sentry craftFreperiving may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)Preservicing may includeDistal pollution of wate material (e.g. concrete and metal parts)Preservicing may includeDistal pollution of water material (e.g. concrete and metal parts)Distal pollution of water material (e.g. concrete and metal parts | Load metrics may include | Centre of gravity |
|---|-----------------------------|---|
| Lift pointsWeightCurrentDepthGradientHazardsObstaclesSelecting, inspecting and preparing air-lift bags may includeChecking attachment lines and points Inspecting the neck Inspecting the outer skin Test fillAction to remove/reduce the tisk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeSolution of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | | Composition |
| Worksite data may includeWeightCurrent Depth Gradient Hazards ObstaclesSelecting, inspecting and preparing air-lift bags may includeChecking attachment lines and points Inspecting the neck Inspecting the neck Inspecting the neck Inspecting the neck Using patrol/sentry craftAction to remove/reduce the vising patrol/sentry craftErecting signage Using patrol/sentry craftEffectively controlling the object's movement may culudeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral) Visual pollution of waste material (e.g. concrete and metal parts)De-servicing may includeDrying Logging work details into equipment logs | | Dimensions |
| Worksite data may includeCurrent Depth Gradient Hazards ObstaclesSelecting, inspecting and preparing air-lift bags may includeChecking attachment lines and points Inspecting the neck Inspecting the neck Inspecting the outer skin Test fillAction to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral) Visual pollution of waste material (e.g. concrete and metal parts)Deservicing may includeDrying Logging work details into equipment logs | | Lift points |
| Depth Gradient Hazards ObstaclesSelecting, inspecting and preparing air-lift bags may includeChecking attachment lines and points Inspecting the neck Inspecting the outer skin Test fillAction to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsFurvironmental impact may versusContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | | Weight |
| GradientHazardsObstaclesSelecting, inspecting and preparing air-lift bags may includeChecking attachment lines and points Inspecting the neck Inspecting the outer skin Test fillAction to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsEnvironmental impact may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | Worksite data may include | Current |
| Hazards ObstaclesSelecting, inspecting and preparing air-lift bags may includeChecking attachment lines and points Inspecting the neck Inspecting the outer skin Test fillAction to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsDispecting the outer skin (Signage) Using patrol/sentry craftEnvironmental impact may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | | Depth |
| Selecting, inspecting and preparing air-lift bags mayObstaclesChecking attachment lines and points Inspecting the neck Inspecting the outer skin Test fillAction to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsFurvironmental impact may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)Pe-servicing may includeDrying Logging work details into equipment logs | | Gradient |
| Selecting, inspecting and preparing air-lift bags may includeChecking attachment lines and points inspecting the neck inspecting the outer skin Test fillAction to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsDiscurptionContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | | Hazards |
| preparing air-lift bags may includeInspecting the neck Inspecting the outer skin Test fillAction to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsEnvironmental impact may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral) Visual pollution of waste material (e.g. concrete and metal parts)De-servicing may includeDrying Logging work details into equipment logs | | Obstacles |
| includeInspecting the neckInspecting the outer skinTest fillAction to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsEnvironmental impact may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral) Visual pollution of waste material (e.g. concrete and metal parts)De-servicing may includeDrying Logging work details into equipment logs | Selecting, inspecting and | Checking attachment lines and points |
| Inspecting the outer skin Test fillAction to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)Pe-servicing may includeDrying Logging work details into equipment logs | | Inspecting the neck |
| Action to remove/reduce the risk may includeErecting signage Using patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsEnvironmental impact may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | include | Inspecting the outer skin |
| risk may includeUsing patrol/sentry craftEffectively controlling the object's movement may includeBoth lateral and vertical adjustmentsEnvironmental impact may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | | Test fill |
| Effectively controlling the object's movement may includeBoth lateral and vertical adjustmentsEnvironmental impact may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | Action to remove/reduce the | Erecting signage |
| object's movement may includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | risk may include | Using patrol/sentry craft |
| includeContamination of surrounding water (e.g. leaking oil) Physical damage to reef and associated floor eco-systems (e.g. coral)De-servicing may includeDrying Logging work details into equipment logs | • | Both lateral and vertical adjustments |
| includePhysical damage to reef and associated floor eco-systems (e.g. coral)Visual pollution of waste material (e.g. concrete and metal parts)De-servicing may includeDrying Logging work details into equipment logs | с | |
| Physical damage to reef and associated floor eco-systems (e.g. coral)Visual pollution of waste material (e.g. concrete and metal parts)De-servicing may includeDrying Logging work details into equipment logs | Environmental impact may | Contamination of surrounding water (e.g. leaking oil) |
| metal parts) De-servicing may include Drying Logging work details into equipment logs | include | |
| Logging work details into equipment logs | | 1 0 |
| | De-servicing may include | Drying |
| Oiling/greasing | | Logging work details into equipment logs |
| | | Oiling/greasing |

RANGE STATEMENT

Washing in fresh water

Unit Sector(s)

Not applicable.

Corequisite Unit/s

Co-requisite Unit/s Nil