



Australian Government

TLID0017 Operate container side lifter

Release: 1

TLID0017 Operate container side lifter

Modification History

Release 1. This is the first release of this unit of competency in the TLI Transport and Logistics Training Package.

Application

This unit involves the skills and knowledge required to operate a container side lifter (swing lifter and/or side loader).

It includes checking a container side lifter and ancillary equipment, ensuring site safety, loading a container from the ground onto a vehicle, unloading a container from vehicle to ground, and transferring a container from one vehicle to another in accordance with relevant state and/or territory authority requirements and regulations.

It also includes maintaining systematic and efficient control of all functions, managing side lifter condition and performance, and effectively managing hazardous situations while operating a container side lifter.

Operation of a container side lifter is performed with limited supervision, and with duty of care responsibility for self and others in achieving the prescribed outcomes.

No licensing, legislative or certification requirements apply to this unit at the time of publication.

Pre-requisite Unit

Not applicable.

Competency Field

D – Load Handling.

Unit Sector

Not applicable.

Elements and Performance Criteria

ELEMENTS

Elements describe the essential outcomes.

PERFORMANCE CRITERIA

Performance criteria describe the performance needed to demonstrate achievement of the element.

- 1 Check a container side lifter and ancillary equipment**
 - 1.1** Job hazards are identified and required actions taken to minimise, control or eliminate identified hazards
 - 1.2** Load lifting capacity for side lifter and ancillary equipment, as required, is identified in terms of maximum rated capacity
 - 1.3** Pre-operational checks and inspections are conducted on side lifter, lifting assemblies, specialist lifting equipment and ancillary equipment, as required, to ensure serviceability and suitability for task and readiness for operation
- 2 Ensure site safety**
 - 2.1** Ground conditions are checked to ensure stability and suitability and overhead obstacles are identified to ensure positioning of side lifter is appropriate and in accordance with workplace policy and procedures
 - 2.2** Site safety is managed in accordance with workplace policy and procedures
 - 2.3** Exclusion zones are identified and implemented
- 3 Load loaded container from the ground onto side lifter vehicle**
 - 3.1** Container weight is checked to ensure it is within specified maximum lifting capacity of side lifter vehicle
 - 3.2** Side lifter is positioned, lifter engine is started, and side lifter readiness for lift, including deployment of stabiliser legs, is completed in accordance with manufacturer specifications and workplace procedures
 - 3.3** Lifting equipment is attached to container, checked and adjusted, as required, in accordance with manufacturer specifications and workplace procedures
 - 3.4** Pre-lift physical check is performed to ensure side lifter is capable of lifting container safely
 - 3.5** Container is lifted and placed onto side lifter twist locks in accordance with manufacturer specifications and workplace procedures
 - 3.6** Loaded container is secured and vehicle is made ready for on-road travel in accordance with regulatory requirements, manufacturer specifications and workplace procedures
- 4 Unload loaded container from side lifter vehicle onto the ground**
 - 4.1** Container weight is checked to ensure it is within side lifter vehicle specified maximum lifting capacity
 - 4.2** Side lifter is positioned, lifter engine is started, and side lifter is made ready for lift, ensuring that deployment of stabiliser

legs is completed in accordance with manufacturer specifications and workplace procedures

- 4.3 Load securing devices are unlocked or removed and lifting equipment is attached to container, checked and adjusted, as required, in accordance with manufacturer specifications and workplace procedures
- 4.4 Pre-lift physical check is performed to ensure side lifter is capable of lifting container safely
- 4.5 Container is lifted and placed on ground, in accordance with organisational requirements, allowing access to the container doors and surroundings
- 4.6 Lifting equipment is removed from container and side lifter vehicle is made ready for on-road travel in accordance with manufacturer specifications and workplace procedures

5 Transfer loaded container from one vehicle to another

- 5.1 Receiving vehicle and container are checked to ensure they are compatible and that receiving vehicle load capacity is adequate for intended load
- 5.2 All vehicles are positioning in accordance with intended transfer requirements
- 5.3 Lifter engine is started, and side lifter is made ready for lift
- 5.4 Load securing devices are unlocked or removed and lifting equipment is attached to container, checked and adjusted, as required, in accordance with manufacturer specifications and workplace procedures
- 5.5 Pre-lift physical check is performed to ensure side lifter is capable of lifting container safely
- 5.6 Container is transferred to receiving vehicle in accordance with manufacturer specifications and workplace procedures
- 5.7 Lifting equipment is removed from container and both vehicles are made ready for on-road travel in accordance with regulatory requirements, manufacturer specifications and workplace procedures
- 5.8 Loaded container is secured in accordance with regulatory requirements and manufacturer specifications
- 5.9 Documentation is completed in accordance with workplace procedures

Foundation Skills

Foundation skills essential to performance are explicit in the performance criteria of this unit of competency.

Range of Conditions

Range is restricted to essential operating conditions and any other variables essential to the work environment.

Non-essential conditions can be found in the TLI Transport and Logistics Training Package Companion Volume Implementation Guide.

Unit Mapping Information

This unit replaces and is equivalent to TLID3046 Operate container side lifter.

Links

Companion Volume Implementation Guides are found in VETNet -

<https://vetnet.gov.au/Pages/TrainingDocs.aspx?q=df441c6e-213d-43e3-874c-0b3f7036d851>