



Australian Government

Assessment Requirements for CPCCPD3036 Work safely to encapsulate non-friable asbestos in the painting industry

Release: 3

Assessment Requirements for CPCCPD3036 Work safely to encapsulate non-friable asbestos in the painting industry

Modification History

- Release 3 Updated reference to general construction induction training program.
- Release 2 This version first released with CPC Construction, Plumbing and Services Training Package Release 6.4.
- Correction to Training Package title in the Modification History from CPC Property Services to CPC Construction, Plumbing and Services Training Package.
- Release 1 This version first released with CPC Property Services Training Package Release 5.0.
- Supersedes and is equivalent to CPCCPD3031A Implement safe lead paint and asbestos work practices in the painting industry. Safe lead practice aspects removed and incorporated into separate unit. Safe treatment of asbestos material strengthened. Updated to meet the Standards for Training Packages 2012.

Performance Evidence

To demonstrate competency, a candidate must meet the performance criteria of this unit by using a paint system to encapsulate at least six square metres of non-friable asbestos.

All work must be performed to the standard required in the workplace and must meet the requirements of work health and safety (WHS), Commonwealth and state or territory legislation, manufacturers' specifications, and environmental plans and obligations.

Knowledge Evidence

To be competent in this unit, a candidate must demonstrate knowledge of:

- industry standards' recommendations for asbestos contamination
- current regulatory requirements and industry standards for encapsulation of asbestos
- responsibilities and limitations when working with asbestos, including when to report the presence of asbestos
- safety requirements relevant to implementing safe asbestos work practices in the painting industry
- personal protective equipment (PPE)
- sources and types of asbestos, including:
 - asbestos-containing materials (ACM)
 - loose-fill asbestos

- naturally-occurring asbestos
- friable and non-friable asbestos
- identifying the presence of asbestos
- environmental requirements relevant to implementing safe asbestos work practices in the painting industry
- building information on asbestos, including asbestos registers
- products for encapsulating asbestos, their uses and limitations
- encapsulation treatments for asbestos, their uses and limitations
- health risks associated with asbestos
- materials storage and environmentally friendly waste management in the painting industry
- processes for the calculation of material requirements.

Assessment Conditions

Assessors must meet the requirements for assessors contained in the Standards for Registered Training Organisations.

This unit must be assessed:

- in the workplace or a close simulation of the workplace environment, provided that simulated or project-based assessment techniques replicate construction workplace conditions, materials, activities, responsibilities and procedures.
- using realistic tasks or simulated tasks, relevant specifications and work instructions, standard work practices, safety requirements and environmental constraints.

Links

Companion volumes to this training package are available at the VETNet website - <https://vetnet.gov.au/Pages/TrainingDocs.aspx?q=7e15fa6a-68b8-4097-b099-030a5569b1ad>