



Australian Government

Assessment Requirements for CPCSH3007 Install prefabricated internal shopfitting units

Release: 2

Assessment Requirements for CPCSH3007 Install prefabricated internal shopfitting units

Modification History

- Release 2 Updated reference to general construction induction training program.
- Release 1 This version first released with CPC Construction, Plumbing and Services Training Package Release 5.0
- Supersedes and is equivalent to CPCCSH3007 Install prefabricated internal shopfitting units.

Performance Evidence

To demonstrate competency, a candidate must meet the performance criteria of this unit by installing four internal shopfitting units. One of these units must be assembled with smaller disassembled components to create a larger unit.

In doing this, the candidate must install:

- one point of sale counter with a minimum size of 2.4 metres in length
- one showcase fitted between walls, floor and ceiling, with a minimum size of 2.0 metres high and 1.8 metres wide, including doors and glass
- one of the following:
 - cabinet with a minimum size of 750 mm high and 2.4 metres wide
 - wall unit with shelves and a minimum size of 1.8 metres high and 1.2 metres wide
 - workstation with a 90-degree return.

Knowledge Evidence

To be competent in this unit, a candidate must demonstrate knowledge of:

- shopfitting regulations, codes and standards
- organisation's quality assurance requirements relating to installation of units
- sustainable shopfitting practices
- content of and terms, symbols and conventions used in working drawings and specifications
- workplace processes and procedures and environmental requirements
- shopfitting units:
 - cabinet
 - counter
 - showcase

- wall unit
- workstation
- characteristics, applications and limitations of materials used in shopfitting components:
 - acrylic
 - glass
 - laminates
 - manufactured board
 - solid timber
- workplace safety:
 - job safety and environmental analysis (JSEA)
 - safe work method statements (SWMSs)
 - hierarchy of control
 - safety data sheets (SDSs)
 - hazardous manual tasks
 - hazardous substances
 - exposure to excessive noise
 - exposure to dust
 - electrical safety
 - emergency procedures (evacuation, location and use of firefighting equipment, first aid)
 - safety of public, visitors and others in the workplace
- processes and techniques for installing shopfitting units:
 - measuring, levelling and plumbing openings
 - selecting and using various fixings and fastenings
- functional and operational features of tools and equipment:
 - levelling equipment
 - air compressor
 - power grinders
 - nail guns
 - power drills
 - battery operated tools
- solving problems, overcoming issues and meeting project schedules.

Assessment Conditions

Assessors must meet the requirements for assessors contained in the Standards for Registered Training Organisations.

Assessment must be conducted in the workplace or a simulated workplace using realistic conditions, materials, activities, responsibilities, procedures, safety requirements and environmental considerations.

Candidates must have access to:

- relevant shopfitting regulations, codes and Australian Standards
- current workplace procedures, workplace safety and environmental documentation
- shopfitting drawings and specifications, organisational policies, procedures and equipment to undertake the performance criteria and assessment requirements
- digital technology, devices and software to communicate with others and to develop and save documents electronically.

Links

Companion volumes to this training package are available at the VETNet website - <https://vetnet.gov.au/Pages/TrainingDocs.aspx?q=7e15fa6a-68b8-4097-b099-030a5569b1ad>