



Australian Government

MSFFL3025 Apply oil-based coatings to timber flooring

Release: 1

MSFFL3025 Apply oil-based coatings to timber flooring

Modification History

Release 1 - New unit of competency

Application

This unit of competency covers selecting oil-based coating systems appropriate for the job, preparing for the work and applying the selected coatings to timber and parquet floors.

Licensing, legislative or certification requirements may apply to this unit and relevant state/territory and local government agencies should be consulted to determine any necessary certification or licensing for undertaking flooring work. Access to construction sites requires certification of general induction training specified by the National Code of Practice for Induction for Construction Work (ASCC 2007).

Pre-requisite Unit

Competency Field

Unit Sector

Flooring technology

Elements and Performance Criteria

Elements describe the essential outcomes.		Performance criteria describe the performance needed to demonstrate achievement of the element.	
1	Identify and prepare for work requirements	1.1	Applicable work health and safety (WHS), legislative and organisational requirements relevant to the application of oil-based coatings to timber flooring are verified and complied with
		1.2	Instructions and/or plans are read and interpreted to identify process required to complete work tasks
		1.3	Oil-based coating material is selected with regard to durability, longevity, aesthetics, manufacturer recommendations and client expectations
		1.4	Selected coating materials are assessed as being compatible with each other, with the surface to be finished and with manufacturer recommendations

- | | | | |
|---|------------------------|-----|--|
| | | 1.5 | Tools, equipment and materials are selected and checked prior to use to ensure that they are appropriate for the work, serviceable and in a safe condition |
| | | 1.6 | Surface to be finished is inspected and assessed as being ready for coating and barrier signs to coating area are erected |
| | | 1.7 | Work sequence is planned to ensure efficiency and quality of application |
| | | 1.8 | WHS requirements, including isolation, ventilation and other personal protection needs, are observed throughout the work |
| 2 | Apply finishing system | 2.1 | Ventilation is checked before chemical fumes are released, and all WHS requirements are met, including use of personal protective equipment |
| | | 2.2 | Environmental protection regulations are complied with |
| | | 2.3 | Oil-based coating material is applied in accordance with manufacturer recommendations |
| | | 2.4 | Recommended drying times between coats are observed |
| | | 2.5 | Buffing or sanding between coats, where required, is carried out according to manufacturer recommendations |
| | | 2.6 | Final finish meets the requirements of the job |
| 3 | Complete housekeeping | 3.1 | Unused materials are resealed and stored |
| | | 3.2 | Tools and equipment are cleaned, maintained and stored |
| | | 3.3 | Work area is cleaned and waste material is removed and disposed of safely |
| | | 3.4 | Barriers and signs are removed and stored |
| | | 3.5 | Workplace documentation/reporting is completed |

Foundation Skills

Foundation skills essential to performance are explicit in the performance criteria of this unit of competency. Detail on appropriate performance levels for each furnishing unit of competency in reading, writing, oral communication and numeracy utilising the Australian Core Skills Framework (ACSF) are provided in the Furnishing Training Package Implementation Guide.

Range of Conditions

Specifies different work environments and conditions that may affect performance. Essential operating conditions that may be present (depending on the work situation, needs of the candidate, accessibility of the item, and local industry and regional contexts) are included. Range is restricted to essential operating conditions and any other variables essential to the work environment.

Unit context includes:	• WHS requirements, including legislation, building codes, material safety management systems, hazardous and dangerous goods codes, and local safe operating procedures or equivalent • work is carried out in accordance with legislative obligations, environmental legislation, relevant health regulations, manual handling procedures and organisation insurance requirements • work requires individuals to demonstrate some discretion, judgement and problem solving
Oil-based coating materials include:	• waxes • oils • oleoresins • one-can urethane oils
Tools and equipment includes:	• orbital sander • rotary sander • hand sander • vacuum cleaner • brushes • applicators • rollers • roller tray • hammer • nail punch • spatula
Surfaces to be finished include:	• traditional tongue and groove strip flooring • gluedown or floating strip flooring • engineered timber flooring • block or mosaic parquet flooring

Surface inspection includes:	• ensuring that surface is free from dust and debris, moisture content is acceptable and stable and any preservatives, protective coatings or other contaminants are adequately removed
Work sequence includes:	• preparation • inspection • coating applications and intermediate steps • finalisation • acceptance inspection
WHS requirements include:	• personal protective equipment which is to include that prescribed under legislation, regulation and enterprise policies and practices, and include: • isolation processes, including barriers, tapes and entry access controls • breathing support and ventilation extraction systems
Application methods include:	• rags • brushes • rollers • applicators • spatula
Information and procedures include:	• workplace procedures relating to the use of tools and equipment • work instructions, including job sheets, cutting lists, plans, drawings and designs • workplace procedures relating to reporting and communication • manufacturer specifications and operational procedures

Unit Mapping Information

Supersedes and is equivalent to LMFFL3404A Apply oil-based coatings to timber flooring

Links

Companion Volume implementation guides are found in VETNet -

<https://vetnet.gov.au/Pages/TrainingDocs.aspx?q=0601ab95-583a-4e93-b2d4-cfb27b03ed73>

Assessment Requirements for MSFFL3025 Apply oil-based coatings to timber flooring

Modification History

Release 1 - New unit of competency

Performance Evidence

- Interpret work order and locate and apply relevant information
- Apply safe handling requirements for equipment, products and materials, including use of personal protective equipment
- Identify materials used in the work process
- Follow work instructions, operating procedures and inspection processes to:
 - minimise the risk of injury to self or others
 - prevent damage to goods, equipment and products
 - maintain required production output and product quality
- Complete at least the application of two (2) different oil-based products to two (2) different timber species
- Identify faults/problems and identify and carry out corrective action
- Use mathematical ideas and techniques to correctly complete measurements, calculate area and estimate material requirements
- Communicate ideas and information to enable confirmation of work requirements and specifications and the reporting of work outcomes and problems, interpret basic plans and follow safety procedures
- Avoid backtracking, work flow interruptions or wastage
- Work with others and in a team by recognising dependencies and using cooperative approaches to optimise work flow and productivity

Knowledge Evidence

- State or territory WHS legislation, regulations, standards and codes of practice relevant to the application of oil-based coating to timber flooring
- Organisational and site standards, requirements, policies and procedures for applying oil-based coatings
- Methods of floor preparation from basic sanding to finishing sanding and edging
- Characteristics of oil-based coatings in relation to ventilation, moisture content and reaction to change of temperature and relative humidity
- Type, characteristics, uses and limitation of oil-based coating materials, including manufacturer recommendations
- Types and uses of floor finishing tools and equipment
- Workplace safety systems related to cork floor finishing processes
- Work flow in relation to the application of oil-based coatings to timber floors
- Environmental protection requirements

- Established communication channels and protocols
- Relevant problem identification and resolution
- Appropriate mathematical procedures for estimation and measurement
- Procedures for the recording, reporting and maintenance of workplace records and information

Assessment Conditions

- Assessors must:
 - hold training and assessment competencies as determined by the National Skills Standards Council (NSSC) or its successors
 - have vocational competency in the furnishing industry at least to the level being assessed with broad industry knowledge and experience, usually combined with a relevant industry qualification
 - be familiar with the current skills and knowledge used and have relevant, current experience in the furnishing industry.
- Assessment methods must confirm consistency of performance over time rather than a single assessment event and in a range of workplace relevant contexts.
- Assessment must be by observation of relevant tasks with questioning on underpinning knowledge and, where applicable, multimedia evidence, supervisor's reports, projects and work samples.
- Assessment is to be conducted on single units of competency or in conjunction with other related units of competency. Foundation skills are integral to competent performance in the unit and should not be assessed separately.
- Assessment must occur on the job or in a workplace simulated facility with relevant process, equipment, materials, work instructions and deadlines.
- Access is required to a realistic finishing requirement, materials, equipment and specifications relevant to the coating application.

Links

Companion Volume implementation guides are found in VETNet -

<https://vetnet.gov.au/Pages/TrainingDocs.aspx?q=0601ab95-583a-4e93-b2d4-cfb27b03ed73>